



**Vienna & Trevi espresso
Cleaning the doser & microswitch**

Remove the water tank & the brew group. Lay the machine on its back. Keep the door of machine open. Look in the space above the position where the funnel of the brew group is located inside the machine. Locate a small catch for the trap door in the ceiling (like the pull down steps for the attic in older homes)

- Place a rag below the trap door. Pull the catch in the doser trap door. The doser is full of ground coffee and will spill on the rag.
- Using a soft long hair brush, clean the area inside the doser and the area around the pin plunger of the microswitch.
- Gently press the flap (#9) back and forth to the left and hear the click of the microswitch pin plunger open and close.
- Pull and release the trap door several times to loosen the fine coffee sticking in points not visible to you, clean the inside of the doser. Then turn to the right to the outlet from the grinder. Use the spoon handle or similar tool to scrape the opening clean.
- Pull the machine back on its feet, replace the brew group, close door and try your next espresso.

Above illustrated instructions made available with courtesy of
authorized dealer for espresso machines, parts and service center for Saeco, Gaggia, LaPavoni, Quick Mill, & UNIC

Services Unlimited, Inc/ Parts Guru

650 North Cannon Avenue, Lansdale, PA 19446
Phone: 215-361-7000; Fax: 215-361-7434; e-mail: granita@rcn.com